



Type of luminaire	
Type of luminaire	Ceiling luminaire.
Photometric body	Single-sided light with 24° beam angle facing down
Characteristics of the luminaire	A luminaire with a wide range of applications mounted on horizontal surfaces, including lighting: wall and facade surfaces, and other architectural concepts

General information	
Materials	Powder painted aluminum cast. Lens - safety glass, transparent. Silicone gasket.
Mounting method	Mounting of the luminaire: 2 holes According to the attached instructions
Terminal	Connection terminals: max 3x2,5mm ² Possibility of connecting the luminaire in loops max 1,5 mm ² Round insulated cable with a diameter of ø7...10,5mm
Type of light source	LED module AC integrated Replaceable (LED only) light source by a professional.
Light control	Phase-dimming (TRIAC) TRAILING EDGE (TE) - LEADING EDGE (LE)
Box dimensions [cm]	12x13x13
Luminaire dimensions [cm]	9x12x12

Technical data	
LED module	Lumens EDC 57C 10W xxx 230V F201 3K (↗ Datasheet)
External control	Dimmers Lumens LED AC (User manual)
Luminaire wattage	10,7W
Luminaire luminous flux	631lm
Efficiency of the luminaire	59lm/W
ULOR	0%
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Flicker of light (Pst LM)	≤0.4
Strobe effect (SVM)	≤0.1
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	50 000h
LED photobiological threat	RG0 or RG1
Power Factor luminaire	PF 0,95
THD factor	30%
Ta Rated temperature	+25°C
Max ambient temperature	-40...+25°C

This product contains light source of energy efficiency class **F** / **EPREL**

Optionally, the luminaire is also available:
 - For the LED color 2700K [1/1]
 - For a different color of the fitting (according to the RAL color palette)
 Terms of sale and other information after contact with the Sales Department of Norlys

Inrush current	44mA / 60ms
----------------	-------------

Files to download	
Photometric LDT files	Photometric IES files
Manual	

Indexes		
Index	Color	RAL
2120AL	ALUMINIUM	9006
2120B	BLACK	9005
2120GR	GRAPHITE	7016
2120W	WHITE	9003