



Type of luminaire

Characteristics of the luminaire Luminaire designed to illuminate stairs, steps, staircases, communication lines, ceiling illumination and many other architectural applications.

General information

Materials	Powder painted aluminum cast. Body - powder painted aluminum cast Lens - safety glass, satin. Silicone gasket.
Mounting method	Fixing of luminaire: 2 holes \varnothing 4,2mm, spacing 97mm.
Terminal	Connection terminals: max 3x2,5mm ² , possibility to connect luminaire in max 3x1,5mm ² . A round wire in the isolation with a diameter of \varnothing 7...10,5mm.
Type of light source	LED module AC integrated
Light control	Phase-dimming (TRIAC).
Box dimensions [cm]	13,5x4,5x12

Technical data

Light source wattage	4W
Luminaire wattage	4W
Lamp luminous flux	439lm
Luminaire luminous flux	123lm
Light source efficiency	109,8lm/W
Efficiency of the luminaire	30,8lm/W
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	>50 000h
LED photobiological threat	RG0 or RG1
Energy Efficiency Index	A++
Power Factor luminaire	PF>0,98
THD factor	< 20%
Ta Rated temperature	+25°C
Max ambient temperature	-35...+45°C
Inrush current	17mA / 60ms

Spare parts

46999566	LED module.
----------	-------------

Files to download

Photometric LDT files	Photometric IES files
Manual	

Indexes

Index	Color	RAL
1341AL	ALUMINIUM	9006
1341GR	GRAPHITE	7016